

TABELE NAWOJOWE ROLETY ZEWNĘTRZNEJ OMEGA-STANDARD
RECOMMENDED BOX SIZE FOR A GIVEN ROLLER SHUTTER
HEIGHT – FRONT MOUNTED ROLLER SHUTTER OMEGA-STANDARD
WICKLUNGEN IN DEN EINZELNEN GROSSEN DER ALUMINIUMKASTEN
– VORBAUROLLADEN OMEGA-STANDARD
ТАБЛИЦА ВАЛОВ ДЛЯ НАРУЖНЫХ РОЛЕТ OMEGA-STANDARD



PA-39, PA-45, PA-52 – aluminium profile 39mm, 45mm, 52 mm (including end caps)

max. width 3,7 m.,
max. surface 8 m²

Box size	width 0 - 2 m			width 2,01 - 2,5 m			max. width 3 m, max. surface 6,5 m ²			max. width 3,7 m., max. surface 8 m ²	
	Maximum height of shutte (including the box size)/cm			Maximum height of shutte (including the box size)/cm			Maximum height of shutte (including the box size)/cm			Maximum height of shutte (including the box size)/cm	
	with automatic bolt (including the box size)/cm	with blocking hanger (including the box size)/cm	with blocking hanger (including the box size)/cm	with automatic bolt (including the box size)/cm	with blocking hanger (including the box size)/cm	with blocking hanger (including the box size)/cm	with automatic bolt (including the box size)/cm	with blocking hanger (including the box size)/cm	with blocking hanger (including the box size)/cm	with automatic bolt (including the box size)/cm	with blocking hanger (including the box size)/cm
ALUMINIUM	PA-39 ø 40-zw.	PA-39 ø 40-rygiel	PA-39 ø 40-WB	PA-39 ø 60-zw.	PA-39 ø 60-rygiel	PA-39 ø 60-WB	PA-45 ø 60-zw.	PA-45 ø 60-rygiel	PA-45 ø 60-WB	PA-52 ø 60-zw.	PA-52 ø 60-WB
SK-137	162	162	142	145	145	0	0	0	0	X	X
SK-165	250	250	242	238	238	199	163	168	168	X	X
SK-180	306	306	310	298	298	282	214	214	214	206	190
SK-205	394	394	402	403	410	359	294	294	294	270	260

PVCV-37, PVC 52 - PVC profile 37mm and 52 mm (including end caps - insert clips)

max. width 1,6 m, max. surface 3 m² max. width 3 m, max. surface 4,5 m²

Box size	max. width 1,6 m, max. surface 3 m ²			max. width 3 m, max. surface 4,5 m ²			max. width 3 m, max. surface 4,5 m ²		
	Maximum height of shutte (including the box size)/cm			Maximum height of shutte (including the box size)/cm			Maximum height of shutte (including the box size)/cm		
	with automatic bolt (including the box size)/cm	with blocking hanger (including the box size)/cm	with blocking hanger (including the box size)/cm	with automatic bolt (including the box size)/cm	with blocking hanger (including the box size)/cm	with blocking hanger (including the box size)/cm	with automatic bolt (including the box size)/cm	with blocking hanger (including the box size)/cm	with blocking hanger (including the box size)/cm
ALUMINIUM	PVC-37 ø 40-zw.	PVC-37 ø 40-rygiel	PVC-37 ø 40-WB	PVC-37 ø 60-zw.	PVC-37 ø 60-rygiel	PVC-37 ø 60-WB	PVC-52 ø 60-zw.	PVC-52 ø 60-rygiel	PVC-52 ø 60-WB
SK-137	165	X	146	157	X	128	X	X	X
SK-165	279	X	338	275	X	227	175	X	175
SK-180	343	X	354	328	X	302	208	X	208
SK-205	386	X	368	386	X	368	293	X	319

If the width of roller shutter exceeds 2m, pipe ø60 is recommended.

